



Product Highlights:

- High-speed PCIe Gen 3x4 interface: 3300MB/s¹ -NVMe 1.4 supported
- M.2 2280 form factor
- Get 6x the speed of a SATA-based SSD³
- Ideal for PC enthusiasts
- Compact and Slim
- Shock and vibration resistant with no moving parts²
- Three-year limited warranty

Capacities:

500GB

(up to 3000MB/s read¹)

1TB

(up to 3300MB/s read¹)

2TB

(up to 3300MB/s read¹)



Boost your computing experience with faster performance

Designed to elevate your PC experience with faster load times and transfer speeds from boot-up to shutdown, the Lexar NM610 PRO M.2 2280 PCIe Gen 3x4 NVMe SSD will boost your computing experience with speeds up to 3300MB/s¹ read. It's supported by the PCIe Gen 3x4 NVMe 1.4 technology standard for higher performance and efficiency.

Get 6x the speed of a SATA-based SSD³. Upgrade to the Lexar NM610 PRO M.2 2280 PCIe Gen 3x4 NVMe SSD and get 6x the speed of a SATA-based SSD³. With PCIe 3.0 and NVMe 1.4 technology standard, and speeds of up to 3300MB/s¹ read, experience faster performance so you can do more in less time.

Ideal for PC enthusiasts. With fast transfer speeds of up to 3300MB/s¹ read, the Lexar NM610 PRO M.2 2280 PCIe Gen 3x4 NVMe SSD is the ideal choice for PC enthusiast upgrading their PCs or building one from scratch.

Compact and slim. Featuring a compact and light M.2 2280 form factor, the Lexar NM610 PRO M.2 2280 PCIe Gen 3x4 NVMe SSD supports easier installation on your laptop or PC.

Built to last. Unlike traditional hard disk drives, the NM610 PRO SSD has no moving parts, so it's built to last. On top of that, it's also shock and vibration resistant², making it one robust and reliable SSD.

Rigorously tested. All Lexar products undergo extensive testing in the Lexar Quality Labs, facilities with thousands of different cameras and digital devices to ensure performance, quality, compatibility, and reliability.

For more than 29 years, Lexar has been a trusted leading global brand of memory solutions. Our award-winning lineup includes memory cards, USB flash drives, card readers, solid-state drives and DRAM. With so many options, it's easy to find the right Lexar solution to fit your needs. Lexar products are available worldwide at major retail and e-tail stores. For more information or support, visit www.lexar.com.

Lexar Retail Sku	Capacity	Region	Single UPC Code	Inner Carton UPC Code	Inner Carton Qty
LNM610P500G-RNNNG	500GB	Global	843367128730	10843367128737	10
LNM610P01T-RNNNG	1TB		843367128723	10843367128720	
LNM610P002T-RNNNG	2TB		843367128716	10843367128713	

¹ Up to 3300MB/s read transfer. Write transfer speed lower. Speed based on internal testing. Actual performance may vary.

² Shock resistant (1500G, duration 0.5ms, Half Sine Wave) and vibration resistant (10~2000Hz, 1.5mm, 20G, 1 Oct/min, 30min/axis (X,Y,Z)). Based on internal testing. Actual performance may vary.

³ Comparison based on internal testing. Actual performance may vary.

Lexar is not liable for any loss of data or images.

NOTE:

Security safeguards, by their nature, are capable of circumvention. Lexar does not guarantee data will be 100% secure from unauthorized access, alteration, or destruction.

Product appearance, performance, software offerings, and packaging may vary depending on ship date and available inventory.

Actual usable memory capacity may vary. 1GB equals 1 billion bytes.

www.lexar.com

©2025 All Rights Reserved. Information, products, specifications, and features are subject to change without notice. Neither Lexar nor Longsys is responsible for omissions or errors in typography or photography. Lexar, the Lexar logo, and all other Lexar trademarks are the property of Longsys Electronics (HK) Co., Ltd. or Shenzhen Longsys Electronics Co., Ltd. All other trademarks are property of their respective owners.

Specifications

Form Factor	M.2 2280
Interface	PCIe Gen 3x4
Speed	500GB sequential read up to 3000MB/s ¹ 1TB sequential read up to 3300MB/s ¹ 2TB sequential read up to 3300MB/s ¹
Operating Temperature	0° to 70° C (32°F to 158°F)
Storage Temperature	-40° to 85° C (-40°F to 185°F)
Shock Resistant	1500G, duration 0.5ms, Half Sine Wave ³
Vibration Resistant	10~2000Hz, 1.5mm, 20G, 1 Oct/min, 30min/axis (X,Y,Z) ³
TBW	500GB: 120TB, 1TB: 240TB, 2TB: 480TB
DWPD	0.535
MTBF	1,500,000 Hours
Dimensions (W x L x H)	80 x 22 x 2.45mm / 3.15"x0.87"x0.10" (with front label)
Weight	9g